

One vision, Two sharp eyes with Our Innovation

MR-6000

Multifunction in
One Instrument

Multifunction Unit



- Multifunction in one instrument
- Speedy Alignment and Mode change
- Sharp LED ring for Ref measurement
- Air flow control for Tonometry
- Pachy measurement to obtain accurate IOP
- Topo function to detect irregular corneal shape.
- Dry eye screening software will be added

One vision, Two sharp eyes with Our Innovation

MR-6000

Multifunction Unit



- Multifunction in one instrument
- Speedy Alignment and Mode change
- Sharp LED ring for Ref measurement
- Air flow control for Tonometry
- Pachy measurement to obtain accurate IOP
- Topo function to detect irregular corneal shape.
- Dry eye screening software will be added

MR-6000 SPECIFICATIONS

Measurement Range

Reflective power

Spherical	-30.00 D ~ +25.00 D (VD = 12.0 mm)
Cylindrical	0 D ~ +/-12.50 D (VD = 12.0 mm)
Axis	0° ~ 180°

Keratometry

Measurement area	5.00 mm ~ 13.00 mm
------------------	--------------------

Tonometry

Measurement range	1 mmHg ~ 60 mmHg (1 hPa ~ 80 hPa)
-------------------	-----------------------------------

Pachymetry

Measurement range	300 μ m ~ 800 μ m
-------------------	---------------------------

Topography

Measurement area	5.50 mm ~ 10.00 mm (Radius of curvature)
------------------	--

Main unit

Display type	10.4-inch color TFT-LCD
Dimensions and weight	312 (W) X 491 (D) X 450 (H)mm, Approx. 23.0 kg
Voltage	100 VAC ~ 240 VAC
Frequency	50/60 Hz
Power consumption	110 VA



Tomey Corporation [Asia-Pacific]
2-11-33 Noritakeshinmachi
Nishi-Ku, Nagoya, 451-0051, Japan
Tel: ++81-52-581-5327
Fax: ++81-52-561-4735
E-Mail: intl@tomey.co.jp

Tomey GmbH [Europe]
Am Weichselgarten 19a
91058 Erlangen Germany
Tel: ++49-9131-77710
Fax: ++49-9131-777120
E-Mail: info@tomev.de

For more information, visit our web site <http://www.tomey.com>